



Knowle Grove

Rotten Row

100m

A4141

A4141

A4141

A4141

Norton Green

The Park

Darley Green

Chessetts Wood

Netherwood

Diversion ENDS

Diverted traffic

Diverted traffic

Diversion ACCESS & EGRESS ONLY

ROAD AHEAD CLOSED

Diversion ENDS

Diversion

Diversion

ROAD AHEAD CLOSED

Diverted traffic

Diverted traffic

ROAD AHEAD CLOSED


ROAD AHEAD CLOSED

Diversion

NOTES:


- All signs and cones to be in accordance with Chapter 8 new roads and street works a code of practice (Red book)
- Works access and egress are indicative, exact locations to be agreed on site.
- Safety zones are to be installed as required as shown by the SAFETY ZONE DIMENSIONS BELOW
- All signs to be located so as not to obscure signs or objects and should be ballasted near to ground level using sand filled heeslan bags or sign straps.
- All sign positions are indicative only and must be accurately positioned on site with good visibility and be clear of obstructions or vegetation at all times.
- Drawing not to scale

DETAIL A



- Notes:
- During darkness, a single warning light to BS EN 12352:2006 should be provided.
  - Traffic cones should conform to diagram 7101.1 and to BS EN 13422.

DETAIL B



- Notes:
- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
  - 45° tapers have 1.5m spacing, no relaxations.
  - On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.



cadrequest@sus.co.uk tmbookings@sus.co.uk

NOTES:

— Diversion  
● Cone  
  Work Area  
  Safety Zone

WORKS ACCESS
WORKS EXIT

Works access/ egress to be positioned to suit ongoing works on site for suitability of location

TRAFFIC MANAGEMENT NOTES

ROAD CLOSURE :

- NOTES
- All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
  - All traffic management equipment shall be provided by the Contractor, unless otherwise specified.
  - All signs shall be positioned so as not to be obscured by any other objects and shall not obscure any other sign, permanent or temporary as much as is reasonably practicable.
  - All traffic signs shall meet the reflectorisation requirements of BS 873 - Part 6 : 1985, Table 1.
  - Works Access/Egress to be positioned to suit ongoing works.

DIVERSION 1

WARWICK ROAD

RISING LANE

PACKWOOD LANE

DIVERSION 2

DARLEY GREEN ROAD

NORTON GREEN LANE

WARWICK ROAD

SPEED OF ROAD:

LONGWAYS: 0.5  
SIDEWAYS: 0.5



A	35	A	10
B	35	B	10
C	35	C	10
D	35	D	10

SITE:

Bakers Ln, Solihull B93 0EA

GRID REF: -----

TITLE: ROAD CLOSURE

SCALE AT A3: NTS	DATE: -----	DRAWN: JB	CHECKED: LS
---------------------	----------------	--------------	----------------

DWG NO: -----	REV NO: 001
---------------	-------------