



DETAIL B (B)

- Single/dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
- Single/dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
- Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 5m.

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) 45t tapers have 1.5m spacing, no relaxations.
- 3) On all highways and both sides of the road, standard and additional works for lead tapers and the flagging wall of lane changes.

DETAIL D (D)

18m

Notes:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) Detail D applies only to relaxation cases.

Two-way working	Standard Normal traffic including buses and HGVs	Restricted: Cars and light vehicles only
6.75m minimum	6.5m minimum	6.5m minimum
3.25-3.50m (depends on wheel range)	3.25m (depends on wheel range)	3.25m (depends on wheel range)
3.0m (in absolute minimum)	2.5m (in absolute minimum)	2.5m (in absolute minimum)

Specials -



Notes -

DIVERSION ROUTE - A34 STRATFORD RD / DOG KENNEL LANE / B4102 TAMWORTH LANE / WATERY LANE

KEY

- Traffic sign
- Traffic cone
- Traffic signals to Diagram 3000.1
- Working Space
- Pedestrian Barrier