



**KEY**

- Traffic sign
- Traffic cone/winder
- Traffic sign to Diagram 3000.1
- Traffic sign to Diagram 610
- Stop/Go board (P702M/P024)
- Temporary reflective road stud
- High intensity flashing beacon complying with Regulation 54 mounted at a height between 800mm and 1500mm above the road surface
- Pedestrian barrier
- Cable crossing protector
- Temporary vehicle restraint barrier

**DETAIL A**

Provisional sign to Diagram 610 above and below cones

Flashing beacon

These only close spaced 750mm or 1m high traffic cones

**DETAIL B**

40mph or less - 450mm traffic cones, spacing 1.5m  
 50mph or more - 750mm traffic cones, spacing 1.5m  
 Motorways and NSL dual with hardshoulders - 750mm traffic cones, spacing 1.5m relaxation 3m

Notes:  
 1) During darkness, regulation 55 lamps should be provided at 9m centres, relaxation for 40mph or less - 15m.  
 2) 45° tapered cones 1.5m spacing, no relaxations.  
 3) On motorways and NSL dual with hardshoulders use top cones for lead taper and facing wall of line changes

**DETAIL C1**

40mph or less - 450mm traffic cones  
 50mph or more and motorways - 750mm traffic cones

Notes:  
 1) During darkness, regulation 55 lamps are to be provided at 9m centres, relaxation for 40mph or less - 15m.

**DETAIL D**

40mph or less - 450mm traffic cones  
 50mph or more and motorways - 750mm traffic cones

Notes:  
 1) During darkness, regulation 55 lamps are to be provided at 15m centres.  
 2) Detail D applies only to relaxation cases.

**Closure** (Red line)  
**Diversion** (Green line)

REV	DESCRIPTION	BY	DATE

**Bellway  
Mull Croft, B36 0QG  
Footpath Closure**

Hereward Rise  
Halesowen  
Birmingham  
B62 8AN  
Tel: 0121 550 3445  
Fax: 0121 550 4640

Drawn by S Hodson	Date 01/03/18	Project No MC001	Dwg No 001
Checked by L Tipper	Date 01/03/18	Plot date 01/03/18	Scale NTS